



SLIXO L-MP

PRODUCT DESCRIPTION:

SLIXO L-MP is a general-purpose lubricating grease based on Lithium Hydroxystearate soap thickener and high-quality mineral base oil. This grease contains antioxidants, rust, corrosion inhibitors, and anti-wear additives. This product is recommended for the lubrication of rolling element bearings, electric motor bearings, water pumps, and sealed-for-life bearings. NLGI 1 and NLGI 2 are designed for general industrial lubrication which can be used through centralized lubrication systems operating at normal temperatures.

APPLICATION

SLIXO L-MP is recommended for the lubrication of rolling-element bearings, electric motor bearings water pumps, and sealed-for-life bearings. These greases are designed for general industrial lubrication which can be used through centralized lubrication systems operating at normal temperatures.

PRODUCT ADVANTAGES

- The operating temperature range is -20°C to 130°C
- Good oxidation and mechanical stability
- Reliable high-temperature performance
- Long storage life
- Good rust and corrosion protection

TYPICAL PROPERTIES:

| PARAMETERS | TEST METHODS | TYPICAL VALUE | | | | | |
|---|--------------|----------------------------|---------|---------|---------|---------|---------|
| | | 000 | 00 | 0 | 1 | 2 | 3 |
| NLGI Grade | - | | | | | | |
| Thickener Type | - | Lithium 12-Hydroxystearate | | | | | |
| Appearance | Visual | Smooth & Homogenous | | | | | |
| Color | Visual | Yellow to Brown | | | | | |
| Work Penetration @25°C | ASTM D217 | 445-475 | 400-430 | 355-385 | 310-340 | 265-295 | 220-250 |
| Copper Strip Corrosion For 24hrs @100°C | ASTM D4048 | 1b max. | 1b max. | 1b max. | 1b max. | 1b max. | 1b max. |
| Dropping Point °C, Min | ASTM D2265 | N/A | N/A | 190 | 190 | 190 | 190 |
| Water Washout Resistance %Wt @79°C | ASTM D1264 | N/A | N/A | N/A | Max 10 | | |
| Emcor Rust Preventive Test | ASTM D6138 | Pass | | | | | |
| Operating Temperature Range, °C | INTERNAL | -20 to 130 | | | | | |
| Base Oil Viscosity @40°C (Cst) | ASTM D445 | 90-110 | | | | | |

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.