



WAXOL AX 100-SYN

PRODUCT DESCRIPTION:

WAXOL AX 100-Syn grease is a high-performance grease developed for use in the food processing industry. It is based on fully synthetic base oil with WAXOL AX 100-Syn thickener and performance additives. WAXOL AX 100-Syn grease has a strong affinity for metal and it is highly stable when operating with heavy loads at high temperatures. It has excellent sealing properties and it is ideal for lubricating bearings subjected to high temperatures and pressures. The operating temperature range is -40°C to 180°C.

APPLICATIONS

WAXOL AX 100-Syn grease is used in bearings that operate at high temperatures, bearings in refrigeration facilities, bearings that require a lubricant with excellent adhesive and sealing properties.

PRODUCT ADVANTAGES

- The operating temperature range is -40°C to 180°C
- Operates at extreme temperatures
- Excellent load-carrying capacity
- Good resistance against water
- Excellent adhesive and sealing properties
- Long-lasting lubrication

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE	
		1	2
NLGI Grade	-	1	2
Thickener Type	-	Al-Complex Thickener	Al-Complex Thickener
Base Oil Type	-	Synthetic	Synthetic
Appearance	Visual	Smooth & Homogenous	Smooth & Homogenous
Color	Visual	Ivory	Ivory
Work Penetration @25°C	ASTM D217	310-340	265-295
Dropping Point °C, Min	ASTM D2265	250	250
Four Ball Weld Load, Kgf, Min	ASTM D2596	250	250
Operating Temperature Range °C	INTERNAL	-40 to 180	
Base Oil Viscosity @40°C (Cst)	ASTM D445	100	100

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.