



WAXOL LC 40-EP-SEMI SYN

PRODUCT DESCRIPTION:

WAXOL LC 40-EP-Semi Syn is a fluid grease for use in centralized lubrication systems on trucks and buses. It is based on highly refined mineral as well as selected synthetic base oils, extreme pressure, and other carefully selected additives to provide excellent protection in all conditions.

APPLICATIONS

This grease is suitable for centralized lubricating installations in utility vehicles as well as for outside working units having long lubrication feed lines. This product is semi-fluid and may also be used for many gear types, where grease lubrication is recommended. It is also used for lubrication of rail vehicle wheels, truck wheel bearings, roller bearings in crushers, mills and mixers general lubrication applications in steel plants, especially hot and cold rolling mills, centralized lubrication systems where grease is supplied to highly loaded lubrication points.

PRODUCT ADVANTAGES

- The operating temperature range is -20°C to 140°C
- Effective extreme pressure properties
- Enhanced load-carrying and wear protection properties
- Good pumpability
- Good water washout properties

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE
NLGI Grade	-	00/000
Thickener Type	-	Lithium-calcium
Appearance	Visual	Smooth & Homogenous
Color	Visual	Red
Base Oil Type	-	Semi Synthetic
Work Penetration @25°C	ASTM D217	440
Copper Strip Corrosion 24hrs @100°C	ASTM D4048	1b
Dropping Point °C	ASTM D2265	N/A
Operating Temperature Range, °C	INTERNAL	-20 to 140
Base Oil Viscosity @40 °C (Cst)	ASTM D445	40.0
Base Oil Viscosity @100°C (Cst)	ASTM D445	7.0

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.