



WAXOL LX 460-EP-SYN

PRODUCT DESCRIPTION:

WAXOL LX 460-EP-Syn is a synthetic, extreme pressure, multi-purpose, semi fluid Lithium Complex formulation fortified with PAO synthetic base oil, polymers, anti-wear agents, tackiness additives, and rust and oxidation inhibitors. This technically advanced grease is specifically designed to perform in a variety of applications and in extreme low temperatures.

APPLICATIONS

WAXOL LX 460-EP-Syn grease is primarily designed for use in on-road and off-road vehicles for the lubrication of wheel end bearings on trucks and trailers. It is also recommended for leaky gearboxes, as well as heavy equipment applications operating in extreme cold temperatures. It is a premium product for use where NLGI 00 grade greases are recommended. This grease is designed for smooth and reliable operation in pressurized auto grease systems where long lines and exposure to low temperatures can affect grease delivery.

PRODUCT ADVANTAGES

- The operating temperature range is from -30°C to 150°C
- Truck and trailer wheel end bearings where NLGI 00 greases are specified
- Recommended for industrial plain and anti-friction bearings operating at high speed
- Good oxidation stability
- Where ultra-low temperatures limit the mobility and pumpability of heavier grades of grease

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE
NLGI Grade	-	00
Thickener Type	-	Lithium Complex
Appearance	Visual	Smooth & Homogenous
Color	Visual	Ivory
Base Oil Type	-	Synthetic
Work Penetration @25°C,	ASTM D217	400-430
Copper Strip Corrosion 24hrs @100°C	ASTM D4048	1b
Dropping Point °C, Min	ASTM D2265	240
Water Washout Resistance %Wt @79°C	ASTM D1264	N/A
Four Ball Weld Load, Kgf, Min	ASTM D2596	315
Emcor Rust Protection Rating	ASTM D6138	1/1
Operating Temperature Range, °C	INTERNAL	-30 to 150
Base Oil Viscosity @40°C (Cst)	ASTM D445	460

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.