



WAXOL PU 100

PRODUCT DESCRIPTION:

WAXOL PU 100 is a multipurpose, high temperature, extreme pressure grease that is specially formulated to provide lubrication for highly loaded ball, roller and plain bearing applications at high temperatures where an extended service life is required. It is also recommended for paper, steel, aluminum, chemical and other industries.

APPLICATIONS

WAXOL PU 100 grease NLGI-2 is also recommended for paper, steel, aluminum, chemical and other industries.

PRODUCT ADVANTAGES

- The operating temperature range is -10°C to 150°C
- Outstanding high-temperature oxidation stability
- Reduced grease consumption at high temperatures
- Protects bearings against wear under conditions of shock loading
- Resists water washing and rusting
- Long operational life

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE
NLGI Grade	ASTM D217	2
Thickener Type	-	Di- Urea
Base Oil Type	-	Mineral
Appearance	Visual	Smooth & Homogenous
Color	Visual	Light Brown
Work Penetration, 0.1 mm	ASTM D217	265-295
Dropping Point, °C, Min	ASTM D2265	>250
Cu Corrosion	ASTM D4048	1b
Oxidation Stability, Drop In Pressure, Psi	ASTM D942	max 5
Heat Stability, % Wt.	ASTM D6184	3 max
Operating Temperature Range °C	INTERNAL	-10 to 150
Base Oil Viscosity @40°C (Cst)	ASTM D445	100

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.