



## SWIFT NOVA FULLY SYNTHETIC

### PRODUCT DESCRIPTION:

SWIFT NOVA is a high-performance synthetic engine oil engineered to meet the latest API SQ and ILSAC GF-7 standards for modern gasoline engines. It delivers exceptional protection against wear, sludge buildup, and LSPI (Low Speed Pre-Ignition), while enhancing fuel efficiency and maintaining engine cleanliness.

### APPLICATION:

Suitable for gasoline engines from North American, European, and Japanese manufacturers, including turbocharged and direct-injection technologies. Recommended for vehicles requiring API SQ, ILSAC GF-7, or earlier specifications such as SP and GF-6. Fully compatible with catalytic converters and ethanol-blended fuels up to E85.

### FEATURES & BENEFITS:

SWIFT NOVA delivers measurable performance advantages over previous GF-6 formulations:

- Provides cleaner pistons through improved oxidation and deposit control.
- Offers better fuel economy and enhanced efficiency.
- Ensures stronger LSPI protection, particularly in aged oil conditions.
- Reduces timing-chain wear, extending engine life.
- Improves low-temperature pumpability for faster lubrication.
- Optimized for GPF readiness and compatibility.
- Delivers robustness against oil gelation and water exposure.
- Enhanced elastomer compatibility with new tested materials.

These benefits combine to deliver outstanding wear protection, deposit control, oxidation resistance, and enhanced emission-system durability for next-generation engines.

### PERFORMANCE LEVELS /MEETS OR EXCEEDS:

- API SQ
- ILSAC GF-7A/B
- API SP (0W-8 Viscosity grade is not applicable to API SP)
- JASO GLV-1

### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	SWIFT NOVA						
			0W-8	0W-16	0W-20	0W-40	5W-30	5W-40	10W-30
Grade			TBR	TBR	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @40 °C	D7042	cSt	5.1	7.1	8.3	13.8	10.3	14.2	10.5
Kinematic Viscosity @100 °C	D7042	cSt	145	150	165	170	160	165	150
Viscosity Index	D2270	–	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Density @15 °C	D4052	g/cm <sup>3</sup>	220	220	220	235	225	235	230
Flash Point (min)	D92	°C	-45	-39	-49	-39	-39	-39	-36
Pour Point (max)	D97	°C							

### DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

### HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

### PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

### STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing temperatures.