



SWIFT C3 PLUS

FULLY SYNTHETIC

PRODUCT DESCRIPTION:

SWIFT C3 PLUS is a premium fully synthetic, mid-SAPS engine oil engineered for modern gasoline and diesel passenger vehicles, including turbocharged and direct-injection engines. Formulated with advanced additive technology, it provides exceptional engine cleanliness, outstanding wear protection, excellent oxidation stability, and effective control of sludge and harmful deposits. It also offers enhanced protection against Low-Speed Pre-Ignition (LSPI) and timing-chain wear while maintaining full compatibility with modern exhaust after-treatment systems, helping to ensure long-term engine performance and reliability.

APPLICATION:

SWIFT C3 PLUS is recommended for modern passenger cars and light commercial vehicles requiring mid-SAPS engine oil meeting ACEA C3 and OEM performance requirements. It is particularly suitable for Euro 4, Euro 5 and Euro 6 gasoline and diesel vehicles fitted with sensitive exhaust after-treatment devices. The product may be used for extended oil-drain intervals only where permitted by the vehicle manufacturer and supported by the vehicle operating conditions.

SWIFT C3 PLUS is suitable for vehicles equipped with:

- Diesel Particulate Filters, DPF
- Gasoline Particulate Filters, GPF
- Three-Way Catalytic Converters, TWC
- Turbochargers
- Gasoline Direct Injection, GDI
- Turbocharged Gasoline Direct Injection, TGT

FEATURES & BENEFITS:

- Advanced protection against LSPI in turbocharged direct-injection gasoline engines
- Enhanced timing-chain wear protection
- Excellent piston, ring-belt and turbocharger cleanliness
- Strong sludge and deposit control
- Reliable wear protection under severe operating conditions
- Mid-SAPS formulation supporting DPF, GPF and TWC durability
- Excellent oxidation resistance and viscosity retention
- Rapid oil circulation during cold starts
- Strong lubricating-film protection at elevated temperatures
- Helps minimize oil consumption through volatility control
- Protection against rust and corrosion
- Suitable for gasoline, diesel and hybrid passenger-car applications where the listed specifications are required

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	0W-30	5W-30	5W-40
API	SP	SP	SP
ACEA	C3-23	C3-23	C3-23
MB	229.31 / 229.51 / 229.52	229.31 / 229.51 / 229.52	229.31 / 229.51 / 229.52
VW	504 00 / 507 00	504 00 / 507 00	–
BMW	Longlife-04	Longlife-04	Longlife-04
PORSCHE	C30	C30	–
OPEL	OV 040 1547-D30 / G30	OV 040 1547-D30 / G30	–

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	SWIFT C3 PLUS		
Grade			0W-30	5W-30	5W-40
Kinematic Viscosity @ 104°F / 40°C	D7042	cSt	TBR	TBR	TBR
Kinematic Viscosity @ 212°F / 100°C	D7042	cSt	11.5	11.5	14.5
Viscosity Index (min)	D2270	–	160	160	165
Density @ 15°C / 60°F	D4052	g/cm³	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220
Pour Point (max)	D97	°C	-39	-39	-39

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing temperatures.